

CK-R4

4CH TNC Port WiFi UHF RFID Reader



4CH TNC Port WiFi UHF RFID Reader applied to RFID tag reading, unique algorithm fast multi-tag identification, support data filtering, multi-protocol expansion. Widely used in vehicle inspection, customs clearance, vehicle inspection, personnel entry and exit, asset entry and exit, electronic tickets, file management, jewelry management, storage management and other fields

- RF channel is based on the special UHF RFID chip R2000 with excellent performance. It has strong expansibility, stable performance and powerful function, and can meet a variety of applications
- This reader has excellent reading performance, the reading distance is up to 20M, the writing distance is up to 10M, and the reading speed is greater more than 500 pcs/s
- Support wireless communication, protection level up to IP66



Specification

Model	CK-RDC1		
RF SPECIFICATION			
Identification Method	UHF		
RF Chip	Impinj R2000		
Frequency Range	840MHz ~ 960MHz		
Protocol	EPC C1G2, ISO 18000-6B, ISO 18000-6C, GB/T29768-2013 (optional)		
Frequency Band (Optional)	ETSI: 865 ~ 868MHz, JP: 916.8 ~ 920.4MHz, TW: 922.25~927.75MHz,ID: 923.125~925.125MHz, RUS: 866.6~867.4 MHz, TEST: 802.75~998.75MHz, JP_LBT: 916.8~920.8MHz(Please tell our sales which band do you want before ordering)		
Communication	RJ45 / RS232 / 12-PIN I/O		
Function	RFID read & write, Multiple label identification, Label data filtering, Quantity statistics, RSSI perception, RF power regulation		
Modulation mode	DSB-ASK, PR-ASK		
RF Interface Power	33dbm+-1dbm (Max)		
R/W Capability	Read: 0-1500 cm; Write: 0-700 cm; 600+ pcs/s		
RF Interface	4 TNC		

| HARDWARE SPECIFICATION

•			
System Support	Android 4.4		
Hardware	4-core Cortex-A9 1.6 GHz, 1G RAM, 8G ROM		
Display	HDMI 1080P@60Hz		
Communication	RJ45 / RS232 / 12-PIN I/O		



Material	Aluminum				
Power Supply	12V / 4A				
Working Humidity	10%RH~90%RH				
Operat Temperature	0 °C ~ 60 °C				
Size	19.5 x 15.4 x 2.7 cm				
FUNCTION SELECT	TION				
Wireless Network	WiFi / 4G Optional				
Bluetooth	Optional				
Material	Aluminum				
Protection level	IP65				




Related ModelCK-R1,CK-R4,CK-R8,CK-R16

Common Solution

Smart Library, Archival Room, Tool Room, Supermarket, etc.

Dimension



Unit : mm (inch) Weight. : about 1kg

Accessory

No.		item	units	quantity
	1	RS232 Serial cable	pcs	1
	2	power supply	pcs	1





RFID IoT Application





Need Advice

Subscribee

Follow us: Cykeo











Headquarters

Cykeo Information Technology CO., LTD.

16th floor, Bullding B2, Yunzhl Science Park, Guangming District,
Shenzhen 518107, China

Factory

Shenzhen, Dongguang, Hefei

Subsidiary

Hefei Jianshen InformationTechnology Co., LTD.

Cykeo Information Technology(Shandong) Co., LTD.

Cykeo Information Technology(Chengdu) Co., LTD.

Cykeo Core Information Technology (Shanghai) Co., LTD.