

CK-TP2B

Assembly Line Batch Bind UHF RFID Tag Device



Industry Batch Bind RFID Tag Device applicable to industrial production, logistics distribution, warehouse and other production lines, the number of items containing RFID tags, label information binding, information proofreading, sound and light alarm and other functions of management, quantity statistics, sound and light alarm and other functions

- 10.1-inch capacitive touch screen with 1366 × 768 resolution
- RFID technology 840~960MHz optional, support protocol extension
- Multiple communication interfaces: RJ45, RS232, USB, alarm input etc
- Support multiple devices in parallel, conveyor speed 33-50cm/s
- The screen generates lists in real time for easy management, optional Windows / Android
- Product appearance, function, protocols etc support customization

● Specification

Model	CK-TP2B
 RF SPECIFICATION	
Identification Method	UHF
RF Chip	Impinj R2000
Frequency Range	840MHz ~ 960MHz adjustable
Protocol	EPC C1G2, ISO 18000-6B, ISO 18000-6C
Frequency Band (Optional)	ETSI: 865 ~ 868MHz, JP: 916.8 ~ 920.4MHz, TW: 922.25~927.75MHz, ID: 923.125~925.125MHz, RUS: 866.6~867.4 MHz, TEST: 802.75~998.75MHz, JP_LBT: 916.8~920.8MHz
Product Capacity	1000 pcs (according of item size)
RF Interface Power	33dbm+-1dbm (Max)
Recognition Response	1-5 seconds
Function	RFID read function, Multiple label identification, Label data filtering, RSSI perception, Quantity statistics

| HARDWARE SPECIFICATION

System Support	Windows / Android (optional)
Hardware	I5 CPU, 4G RAM, 128G ROM RK3399 CPU, 4GRAM, 16G ROM (optional)
Display	1366 x 768, 10.1-inch capacitive touch screen
Communication	RJ45, RS232, USB

| FUNCTION SELECTION

RFID Card Reader	Standard
Bar Code	Optional
QR Code	Optional
Fingerprint Recognition	Optional
Face Recognition	Optional

CCTV Camera	Optional
Solar Energy	Optional
Sound Light Alarm	Optional
Wireless Network	WiFi / 4G


BASIC SPECIFICATION

Material	Sheet metal spray paint
Conveyor Speed	33-50 cm/s
Bearing Capacity	50 kg
Power Supply	AC 110-220V 50Hz 50W
Working Humidity	10%RH~90%RH
Operat Temperature	0 °C ~ 60 °C
Size	351 x 137 x 127 cm

- **Related Model**
CK-TP1

- **Common Solution**
Smart Library, Archival Room, Tool Room, Supermarket, etc.

- **Dimension**



Unit : mm (inch)
Weight. : about
150kg

- **Accessory**

No.	item	units	quantity
1	power supply	pcs	1



RFID IoT Application



Need Advice



Subscribee

Follow us: Cykeo



Headquarters

Cykeo Information Technology CO., LTD.

16th floor, Building B2, Yunzhi Science Park, Guangming District,
Shenzhen 518107, China

Factory

Shenzhen, Dongguang, Hefei

Subsidiary

Hefei Jianshen InformationTechnology Co., LTD.

Cykeo Information Technology(Shandong) Co., LTD.

Cykeo Information Technology(Chengdu) Co., LTD.

Cykeo Core Information Technology (Shanghai) Co., LTD.